

HGS-Serie mit Halogenlampen
HGS-Series with Halogen Lamps

Scheinwerferkopf Ømm = „G” Searchlight head	Eingangsspannung Volt Inputpower	Spiegel „Ø”mm Reflector	Abmessungen / Measurement (mm)								Gewicht kg Weight.
			Gleich # the same bei # at 80/100mm Ø								
			A	B	C	D	E	F	G	H	
DS	24VDC/AC ●	180mm	400	505	360	320				273	10
DH	110VAC		400	1425	1280	320				273 1000	20
WS	230VAC ○		400	545	400	320	500	300		273	16
WH	440VAC		400	1425	1280	320	500	300		273 1000	25
DS	24VDC/AC ●	250mm	485	645	470	390				351	14
DH	110VAC ○		485	1550	1375	390				351 1000	24
WS	230VAC ●		485	670	495	390	500	300		351	20
WH	440VAC		485	1550	1375	390	500	300		351 1000	29
DS	24VDC/AC ○	360mm	610	820	575	470				463	22
DH	110VAC ○		610	1725	1480	470				463 1000	32
WS	230VAC ●		610	845	600	470	500	300		463	27
WH	440VAC ○		610	1725	1480	470	500	300		463 1000	37
DS	24VDC/AC ○	420mm	665	895	633	565				525	26
DH	110VAC ○		665	1800	1538	565				525 1000	36
WS	230VAC ●		665	920	658	565	500	300		525	32
WH	440VAC ○		665	1800	1538	565	500	300		525 1000	41

XBO-Serie mit Xenon-Kurzbogenlampen
XBO-Series with Xenon Short-Arc Lamps

Typ / Type	Eingangsspannung Volt Inputpower	Spiegel „Ø”mm Reflector	Abmessungen / Measurement (mm)								Scheinwerfer Searchlight	Stromversorgung Power Supply
			Gleich # the same bei # at 80/100mm Ø								Gewicht kg. Weight	Gewicht kg. Weight
			A	B	C	D	E	F	G	H		
DS	110VAC		485	645	470	390				351	28	25
DH	230VAC ●		485	1550	1375	390				351 1000	38	25
WS	440VAC	250mm	485	670	495	390	500	300		351	34	25
WH	X		485	1550	1375	390	500	300		351 1000	42	25
DS	110VAC ○		610	820	575	555				463	36	30
DH	230VAC ●		610	1725	1480	555				463 1000	46	30
WS	440VAC ○	360mm	610	845	600	555	500	300		463	42	30
WH	X		610	1725	1480	555	500	300		463 1000	51	30
DS	110VAC ○		665	895	633	625				525	40	
DH	230VAC ●		665	1800	1538	625				525 1000	50	1000W=44kg.
WS	440VAC ○	420mm	665	920	658	625	500	300		525	46	2000 W=60kg.
WH	X		665	1800	1538	625	500	300		525 1000	55	

