

DET NORSKE VERITAS

TYPE APPROVAL CERTIFICATE

CERTIFICATE NO. E-8738

This Certificate consists of 4 pages

This is to certify that the

Low Voltage Cable

with type designation(s)

**U-HFFRT m, U-HFFRT m(I), U-HFFRT m(C), U-HFFRT
m(I+C)**

Manufactured by

Unika Universal Kablo San.Tic.A.S.

ISTANBUL, Turkey

is found to comply with

Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Det Norske Veritas' Offshore Standards

IEC 60092-376 (2003-05)

IEC 60331-21 (1999-04)

IEC 60332-3-22 (2000-10)

IEC 60754-1 (1994-01)

IEC 60754-2 (1997-04)

IEC 61034-2 (2005-04)

Application


Instrumentation, Control and Communication. Screened. Twisted. Fire Resistant. Halogen free. Low smoke.

Type	Voltage class (V)	Temp. class (°C)
U-HFFRT m	250	90
U-HFFRT m(I)	250	90
U-HFFRT m(C)	250	90
U-HFFRT m(I+C)	250	90

Place and date

Høvik, 2007-11-29

for DET NORSKE VERITAS AS



Marit Laumann

Head of Section



Local Office


DNV Istanbul

This Certificate is valid until

2011-12-31



Ivar Bull

Surveyor 

Notice: This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

If any person suffers loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 2 million. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.



Cert. No.: E-8738

File No.: 827.20

Product description

Type: U-HFFRT m & U-HFFRT m (C) & U-HFFRT m (I) & U-HFFRT m (I+C) 250 V

Construction:

Conductors: Tinned stranded copper class 2 or class 5

Core insulation: Mica tape + XLPE

Screen: Metal coated polyester tape w/plain or tinned copper drain wire (C) or (I) or (I+C)

Inner covering: Tape

Outer sheath: SHF1

U-HFFRT m

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
1 x 2 x 0,5	6,5
1 x 2 x 0,75	7,3
1 x 2 x 1,0	7,7
1 x 2 x 1,5	8,9
1 x 2 x 2,5	9,7
2 x 2 x 0,5	9,4
2 x 2 x 0,75	10,8
2 x 2 x 1,0	11,5
2 x 2 x 1,5	13,2
2 x 2 x 2,5	14,8
3 x 2 x 0,5	10,0
3 x 2 x 0,75	11,6
3 x 2 x 1,0	12,3
3 x 2 x 1,5	14,2
3 x 2 x 2,5	15,7
4 x 2 x 0,5	10,9
4 x 2 x 0,75	12,7
4 x 2 x 1,0	13,4
4 x 2 x 1,5	15,6
4 x 2 x 2,5	17,5
7 x 2 x 0,5	13,1

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
7 x 2 x 0,75	15,3
7 x 2 x 1,0	16,2
7 x 2 x 1,5	18,9
7 x 2 x 2,5	21,1
10 x 2 x 0,5	16,1
10 x 2 x 0,75	18,9
10 x 2 x 1,0	20,2
10 x 2 x 1,5	23,5
10 x 2 x 2,5	26,3
19 x 2 x 0,5	20,7
19 x 2 x 0,75	24,3
19 x 2 x 1,0	26,0
19 x 2 x 1,5	30,5
19 x 2 x 2,5	34,1
37 x 2 x 0,5	28,3
37 x 2 x 0,75	33,5
37 x 2 x 1,0	35,7
37 x 2 x 1,5	41,9
37 x 2 x 2,5	47,1
1 x 3 x 0,5	6,8
1 x 3 x 0,75	7,7

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
1 x 3 x 1,0	8,1
1 x 3 x 1,5	9,4
1 x 3 x 2,5	10,3
2 x 3 x 0,5	10,4
2 x 3 x 0,75	12,2
2 x 3 x 1,0	12,9
2 x 3 x 1,5	14,9
2 x 3 x 2,5	16,7
3 x 3 x 0,5	11,3
3 x 3 x 0,75	12,9
3 x 3 x 1,0	13,9
3 x 3 x 1,5	15,9
3 x 3 x 2,5	17,8
4 x 3 x 0,5	12,3
4 x 3 x 0,75	14,4
4 x 3 x 1,0	15,2
4 x 3 x 1,5	17,7
4 x 3 x 2,5	19,8
7 x 3 x 0,5	14,9
7 x 3 x 0,75	17,4
7 x 3 x 1,0	18,4



Cert. No.: E-8738

File No.: 827.20

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
7 x 3 x 1,5	21,4
7 x 3 x 2,5	24,0
10 x 3 x 0,5	18,3
10 x 3 x 0,75	21,4
10 x 3 x 1,0	22,9
10 x 3 x 1,5	26,7
10 x 3 x 2,5	30,1
19 x 3 x 0,5	23,5
19 x 3 x 0,75	27,7
19 x 3 x 1,0	29,4
19 x 3 x 1,5	34,5
19 x 3 x 2,5	38,9
1 x 4 x 0,5	7,4
1 x 4 x 0,75	8,6
1 x 4 x 1,0	9,0
1 x 4 x 1,5	10,2

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
1 x 4 x 2,5	11,4
2 x 4 x 0,5	12,9
2 x 4 x 0,75	15,1
2 x 4 x 1,0	16,0
2 x 4 x 1,5	18,6
2 x 4 x 2,5	20,9
3 x 4 x 0,5	14,0
3 x 4 x 0,75	16,1
3 x 4 x 1,0	17,3
3 x 4 x 1,5	20,1
3 x 4 x 2,5	22,5
4 x 4 x 0,5	15,3
4 x 4 x 0,75	17,9
4 x 4 x 1,0	19,0
4 x 4 x 1,5	22,3
4 x 4 x 2,5	25,0

Number of cores x conductor cross-section mm ²	Overall Diameter ±10 % mm
7 x 4 x 0,5	18,5
7 x 4 x 0,75	21,7
7 x 4 x 1,0	23,2
7 x 4 x 1,5	27,0
7 x 4 x 2,5	30,5
10 x 4 x 0,5	23,1
10 x 4 x 0,75	27,0
10 x 4 x 1,0	28,9
10 x 4 x 1,5	33,9
10 x 4 x 2,5	37,9
19 x 4 x 0,5	29,7
19 x 4 x 0,75	35,0
19 x 4 x 1,0	37,4
19 x 4 x 1,5	44,1
19 x 4 x 2,5	49,5

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Data sheets and drawings:

- Data sheet and drawing U-HFFRT m
- Data sheet and drawing U-HFFRT m (I)
- Data sheet and drawing U-HFFRT m (C)
- Data sheet and drawing U-HFFRT m (I+C)



Cert. No.: E-8738

File No.: 827.20

Test reports:

IEC60331-21 No. 813 dated 28.09.2007.

Electrical and physical routine test report No. 07650 dated 28.09.2007.

Tests carried out

Type test according to IEC 60092-376, IEC 60331-21, IEC 60332-3-22, IEC 60754-1/2 and IEC 61034-1/2.

Marking of product

Product to be marked: UNIKA KABLO - U-HFFRT m or U-HFFRT m (I) or U-HFFRT m (C) or U-HFFRT(I+C) - size – 250V

Certificate retention survey

The scope of the retention/renewal survey is to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routines (RT) checked (if not available tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Survey to be performed at least every second year.

END OF CERTIFICATE