

DN	L	B	A	a	C	øK	øD	Weight
40	223	213	263	222	428	110	150	16kg
50	223	213	263	222	428	125	165	18kg
65	223	213	263	222	428	145	180	20kg
80	257	270	310	255	507	160	200	26kg
100	257	270	310	255	507	180	220	28kg
125	304	302	335	280	518	210	250	35kg
150	366	385	448	356	683	240	285	55kg
200	461	470	517	425	808	295	340	76kg
250	536	590	660	530	1005	350	395	111kg

All measurements in mm.


Pos	Item	Material	
		Spec. 1	Spec. 2
1	Opening lever	316L	316L
2	Hand lever	316L	316L
3	Body	Hot dip galv.	Aisi 316L
4	Cover	Hot dip galv.	Aisi 316L
5	*Screen	Aisi 316L	Aisi 316L
6	Screen clip	Aisi 316L	Aisi 316L
7	Flange	Hot dip galv.	Aisi 316L

*Option: flame, bug or rat screen

Option: different flange connections available

Approved by major classification societies.

This drawing/specification is the property of JOHN GJERDE AS and must neither be used, reproduced or handed over to a third party without our permission.

Revision		Revision		Scale	Date	Sign.
				%	16.02.10	MGS
					16.02.10	MGS
					16.02.10	MGS
 www.gjerde.com				Draw. no.		
Title AERO 1.3 Tank vent check valve Flanged type – PN10				S-20546-17		