



DN	L	B	A	a	øK	øD	Weight
40	223	213	419	378	110	150	17kg
50	223	213	419	378	125	165	18kg
65	223	213	419	378	145	180	20kg
80	257	270	456	401	160	200	27kg
100	257	270	456	401	180	220	36kg
125	304	302	510	455	210	250	36kg
150	366	385	599	513	240	285	53kg
175	411	430	621	536	270	315	68kg
200	461	470	669	580	295	340	81kg
250	536	590	814	687	350	395	126kg
300	681	685	877	734	400	445	157kg
350	766	885	1056	872	460	505	227kg
400	766	885	1056	872	515	565	266kg

All measurements in mm.

Pos	Item	Material	
		Spec. 1	Spec. 2
1	Body	Hot dip galv.	Aisi 316L
2	Cover	Hot dip galv.	Aisi 316L
3	*Screen	Aisi 316L	Aisi 316L
4	Screen clip	Aisi 316L	Aisi 316L
5	Screw cap	Hot dip galv.	Aisi 316L
6	Flange	Hot dip galv.	Aisi 316L

*Option: flame, bug or rat screen

Option: different flange connections available

Approved by major classification societies.

This drawing/specification is the property of JOHN GJERDE AS and must neither be used, reproduced or handed over to a third party without our permission.

Revision		Revision		Scale	Date	Sign.
				%	02.02.10	MGS
					S-20551-18	
					02.02.10	MGS
					02.02.10	MGS
Mar.Dir.	Class	Owner	Title			
			AERO 1.4			
Appr.			Tank vent check valve with screw cap			
			Flanged type - PN10			
			Draw. no.			
			S-20551-18			

