

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Low Voltage Cable

with type designation(s)

MarineCom YOZc X-FR 250 V, Marine2Com YOZ2c X-FR 250 V

Issued to

**B.V. Twentsche Kabelfabriek
Haaksbergen, Netherlands**

is found to comply with

DNV GL rules for classification – Ships and offshore units

Application :

Control and instrumentation.

Fire resistant.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Type	Voltage class (V)	Temp. class (°C)
MarineCom YOZc X-FR 250 V	250	90
Marine2Com YOZ2c X-FR 250 V	250	90

This Certificate is valid until **2021-01-06**.

Issued at **Høvik** on **2016-01-07**

DNV GL local station: **Rotterdam**

Approval Engineer: **Ivar Bull**



for **DNV GL**

Digitally Signed By: Laumann, Marit

Location: DNV GL Høvik, Norway

Signing Date: 2016-01-08

Marit Laumann

Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

Types: MarineCom YOZc X-FR 250 V c = common screen
Marine2Com YOZ2c X-FR 250 V 2 = individual screen

Construction:

Conductors: Plain stranded copper class 2
Core insulation: Mica tape plus XLHFFR (HF90)
Common Screen: Aluminium foil with tinned copper drain wire
Individual screen (if any) Aluminium foil with tinned copper drain wire
Inner covering: Non hygroscopic tape
Metal covering: Tinned or plain copper wire braid
Outer sheath: SHF1

No of cores:	Cross sectional area [mm ²]
1-37 pairs	0,50 0,75 1,0 1,5 2,5
1-24 triples	0,50 0,75 1,0 1,5 2,5
1 quad	0,50 0,75 1,0 1,5 2,5

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publications 60331-1/2.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Data sheets: MarineCom YOZc X-FR 250 V, Ver. 7 dated 2011-09-05
Marine2Com YOZ2c X-FR 250 V, Ver. 7 dated 2011-09-05

Test reports: TKF Rapport no. 445 dated 2011-05-12

Tests carried out

IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-376	2003-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60331-1/2	2009-05	Fire resistance / Circuit integrity – Test for method for fire <i>with shock</i> at temperature of at least 830°C for cables rated up to and including 0,6/1 kV	Minimum 90 min. test.
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen:

Job Id: **262.1-011803-3**
Certificate No: **TAE00000V3**

IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free:
IEC 61034-1/2	2005-04	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Minimum 60% light transmittance.
IEC 60684-2	2011-08	Flexible insulating sleeving – Part 2: Methods of test Clause 45.2 Methods of determination of low levels of fluorine	HF max 0,1% [0,02% can be detected]

Marking of product

TKF- Size – 250V MarineCom YOZc X-FR X-FR- HALOGEN FREE –IEC 60331–IEC 60332-3-22 -Lot. No or
TKF- Size – 250V Marine2Com YOZ2c X-FR X-FR- HALOGEN FREE --IEC 60331–IEC 60332-3-22 Lot. no

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routine Tests (RT) checked
- (if RT- and PST-test reports are not available, tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensure traceability between manufacturer's product type marking and Type Approval Certificate.

Assessment shall be performed at least every second year.

END OF CERTIFICATE

