

Certificate No: **TAE00003S8** 

# TYPE APPROVAL CERTIFICATE

This is to certify:							
That the Electric Power Ca	ible						
with type designation(s) GAALSHIP HF1000A, GAAL	LSHIP HF1000A EMC						
	sued to LETTROTEK KABEL S.p.A agnolo in Piano RE, Italy						
is found to comply with <b>DNV GL rules for classifica</b>	ntion – Ships, offshor	e units, and high sp	peed and light craft				
Application :							
Product(s) approved by the by DNV GL.	nis certificate is/are a	accepted for install	ation on all vessels classed				
Type GAALSHIP HF1000A GAALSHIP HF1000A EMC	Rated voltage (kV) 0,6/1 0,6/1	Temp. class (°C) 90 90					
Issued at <b>Høvik</b> on <b>2020-0</b> This Certificate is valid until 2 DNV GL local station: <b>Italy/</b>	2025-01-21.		for <b>DNV GL</b>				
Approval Engineer: <b>Georgy</b>	Abramenko						

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 1 of 3

Marta Alonso Pontes Head of Section

Job Id: **262.1-026704-1** Certificate No: **TAE00003S8** 

# **Product description**

Type: GAALSHIP HF1000A, HF1000A EMC

Construction:

Conductors: Plain or tinned annealed flexible copper, class 2 or 5

Core insulation: XLPE

Separator: Mylar tape between cores and armour Armour: Plain or tinned copper wire braid

Tape: Copper backed polyester tape (EMC version only)

Outer sheath: SHF1

#### HF 1000A & HF 1000A EMC cables:

THE TOOGN WITH TOOGN EINE CADICS.				
Number of cores	Conductor cross-section			
1 2 3 4 5	1 1,5 2,5 4 6 10 16 25 35 50 70 95			
1 3 4	120 150 185 240			
1 3	300			
7 10 12 14 16 19 24 27 30 37	1 1,5 2,5			

#### HF 1000A EMC cables:

3 x phases conductor	3 x ground conductor	
cross sections	cross-sections	
16 25 35	6	
50	10	
70 95	16	
120 150	25	
185	35	
240 300	50	

# Application/Limitation

General power and lighting. Halogen free. Low smoke.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation

## **Tests carried out**

Standard	Issued	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of	
		power, control and instrumentation cables for	
		shipboard and offshore applications	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353:	
		Power cables for rated voltages 1 kV and	
		3 kV	
IEC 60754-1	2011-11	Test on gases evolved during combustion of	Low Halogen:
		materials from cables - Part 1: Determination	<0,5% Halogen
		of the halogen acid gas content	
IEC 60754-2	2011-11	Test on gases evolved during combustion of	Halogen free:
		materials from cables - Part 2: Determination	pH > 4,3
		of acidity (by pH measurement) and	Conductivity <
		conductivity	10μS/mm

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 2 of 3

Job Id: **262.1-026704-1** Certificate No: **TAE00003S8** 

Standard	Issued	General description	Limitation
IEC 61034-1/2	2013-06	Measurement of smoke density of cables	Low smoke
		burning under defined conditions –	Light
		Test apparatus, procedure and requirements	transmittance >60%
IEC 60332-1-2	2015-07	Tests on eletric cables under fire conditions.	
		Test for vertical flame propagation for a single	
		insulated wire or cable.	
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under	Charred portion of
		fire conditions – Part 3-22: Test for vertical	sample does not
		flame spread of vertically-mounted bunched	exceed 2,5m above
		wires or cables – Category A	bottom edge of
			burner.

# Marking of product

ELETTROTEK KABEL GAALSHIP - cable type - nominal cross section - voltage - item code n - IEC 60092-353 - IEC 60332-3-22 - batch no - production date - meter marking - production plant\*

#### **Periodical assessment**

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

**END OF CERTIFICATE** 

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 3 of 3

<sup>\*-</sup> A48 - DNV-GL ID 10612009.