

# TYPE APPROVAL CERTIFICATE

Certificate No: **TAP00001U5**Revision No:

This is to certify:

That the Vent Head for Tank

with type designation(s) Aero 1.1, 1.3, Aero 1.2

Issued to

John Gjerde AS GJERDSVIKA, Norway

is found to comply with

DNV class programme DNV-CP-0187 – Type approval – Air vent heads DNV rules for classification – Ships Pt.4 Ch.6 Piping systems DNV-OS-D101 – Marine and machinery systems and equipment, Edition July 2021

## Application:

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV.

Type: Sizes:

Aero 1.1, 1.3 DN 50,65,80,100,125,150,200,250,300,350 & 400 DN 50,65,80,100,125,150,200,250,300,350 & 400

Issued at Høvik on 2022-07-01

This Certificate is valid until 2027-06-30. for DNV

DNV local station: Ulsteinvik

Approval Engineer: Jane Lozanov

Zeinab Sharifi Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2021-03 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-007074-9** Certificate No: **TAP00001U5** 

Revision No: 1

## **Product description**

Self-closing air vent head w/ non-metallic float disc on guiding pin and wire mesh. The air vent head might be equipped with heating element.

Materials:

Body/Cover/Guide pin: S235JR+N (Hot dip galvanized) / Aluminium-5083-H111

Float: ABS Plastic

Manufactured by: Saldus Welding in Saldus, Latvia.

# **Application/Limitation**

The certificate covers design assessment of air vent heads. Installation and other additional requirements related to installation are out of scope of this certificate.

Air vent heads made of galvanized steels shall be protected by hot dip galvanizing. The zinc layer shall be 70 to 100 microns.

The air vent heads are not considered as devices to prevent the passage of flame into cargo tanks. They shall not be installed on oil tanks (flash point<60°C).

Heating elements functionality is not a part of this approval.

Size	80% of blocking velocity at Discharge test (m/s)		Dynamic coefficient (ζ) resulted from flow characteristic tests at ΔP (mmWG)  Aero 1.1 / 1.3  Aero 1.2			
	Aero 1.1 / 1.3	Aero 1.2	ΔΡ	ζ	ΔΡ	ζ
DN50	17.07	38.16	4500	49.34	4000	8.77
DN65	15.35	17.49	4000	16.12	4000	25.05
DN80	17.13	20.00	4500	12.07	4200	3.11
DN100	11.09	13.49	4300	6.92	4200	7.59
DN125	9.81	10.92	3800	24.29	3700	9.69
DN150	12.58	10.39	4500	14.66	4500	5.22
DN200	13.19	23.65	4500	19.67	4500	12.00
DN250	19.30	17.75	3400	13.17	2000	9.16
DN300	19.31	13.40	4000	17.01	2000	20.07
DN350	18.72	14.45	3500	10.26	3200	11.90
DN400	13.69	12.03	2500	21.16	2000	17.77

# Type Approval documentation

### **Tests carried out**

Flow Characteristics test, leakage test, discharge/reverse flow test, compression test of float, float impact test.

# Marking of product

For traceability to this type approval the products are to be marked:

- Manufacturer's name or trade mark
- Type designation
- Size

#### Periodical assessment

For retention of the Type Approval, a DNV Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNV-CP-0338.

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 2 of 2